

Stuv 6-IN 4655

Fitted device or open fire without a hot water supply
complying with the EN 13229: 2001 / A2: 2004 standard
Recommended fuel: wooden logs only

Manufactured by:

Stuv s.a

Rue Jules Borbouse, 4 B-5170 Bois-de-Villers
Tel.: +32(0)81.43.47.96 – Fax: +32(0)81.43.48.74
info@stuv.com www.stuv.com

Approved certifying body:

0608 – SGS Nederland bv
Leemansweg 51 NL-6827 BX Amhem

System to assess and check the consistency of performance: 3
Test report number: EZKA/2019-04/00010-3 & EZKA/2019-04/00010-4
Document number: 10 QA191322924-EN



European standards	EN 13229:2001/A2:2004/AC:2007		
Main features	Performance		
CO emissions	0,08 %		
Smoke temperature at nominal power	225 °C		
Heating power	Nominal:	4,9 kW	
	Distributed in the room:	4,9 kW	
	Distributed in water:	- kW	
Output	80 %		
Maximum water pressure when operating	-		
Surface temperature	Pass		
Surface temperature	Pass		
Electrical safety	Pass		
Mechanical resistance (for the pipe to withstand)	NPD		
Fire safety			
Reaction to fire	A1		
Minimum distances in relation to combustible materials	Rear insulation thickness	40 mm	
	Side insulation thickness	80 mm	
	Top insulation thickness	110 mm	
	Minimum distance to the front	1500 mm	
	Insulation thickness in relation to the floor	50 mm	
Fire risk after burning fuel has fallen	Pass		

Bois-de-Villers, 2023

Gérard Pitance

Chief Executive and Founder

Jean-François Sidler

Managing Director and Chief Executive